

NEW



# FRM220-2000MS

100/1000Base-T to 100/1000Base-X SFP Web Smart In-Band Managed GbE Switch

(Replacement for: FRM220-1000MS)

The FRM220-2000MS is an IEEE 802.3ah OAM compliant copper to fiber Gigabit Ethernet solution designed to make conversion between 10/100/1000Base-T and 100/1000Base-X with SFP modules. With SNMP and Web-based management in the FRM220, the administrator can monitor, configure and control the activity of each series card and remotely connected OAM compliant converter. Converter settings include bandwidth control, duplex, and speed configuration, VLAN tagging, limited Q-in-Q support and SFP DDMI. When used as stand-alone converters, the 2000MS can be managed by a friendly Web Smart user interface via any web browser.

## Features


- 1-Port 10/100/1000Base-T to 100/1000Base-X SFP Converter
- Auto-Cross over for MDI/MDIX in TP port
- Auto-Negotiation or manual mode in TP port
- Supports flow control Enable or Disable
- Supports Jumbo Frame 16K Packet
- Ingress/Egress bandwidth control
- Supports in-band IEEE 802.3ah management
- Firmware upgrade via Web (for standalone unit only)
- Management Password Setting (for standalone unit only)
- Dying gasp (remote power failure detection on stand-alone)
- Supports Link Fault Pass-Through (LFPT) Function
- Supports Auto Laser Shutdown (ALS) Function
- Supports D/D function for SFP fiber transceiver
- Supports 16 Tag VLAN Group
- RMON counters (for standalone unit only)
- USB Console port, Telnet, SNMP, Web Management

## Specifications

Optical Interface	Connector	SFP LC
	Data rate	125/1250Mbps
	Duplex mode	Full duplex
	Fiber	MM 50/125µm, 62.5/125µm SM 9/125µm
	Distance	MM 2km, SM 15/30/50/80/120km WDM 20/40/60/80km
	Wavelength	MM 1310nm, SM 1310,1550nm WDM 1310Tx/1550Rx (type A) 1550Tx/1310Rx (type B)
Electrical Interface	Connector	RJ45
	Data rate	10Mbps, 100Mbps, 1000Mbps
	Duplex mode	Half / Full duplex
	Cable	10Base-T Cat.3, 4, 5, UTP, 100Base-TX Cat.5, 5e or higher 1000Base-TX Cat.6 or higher

<b>Standards</b>	IEEE 802.3, IEEE 802.3u IEEE 802.3ab, 802.3z, 802.3ah, 802.1Q
<b>Indications</b>	LED (Power, FX-Link, LAN Speed, LAN Link)
<b>Power Input</b>	12VDC
<b>Power Consumption</b>	< 6W
<b>Dimensions</b>	159.5 × 20.8 × 88mm (D×W×H)
<b>Weight</b>	120g
<b>Temperature</b>	0 ~ 50°C (Operating), -10 ~ 70°C (Storage)
<b>Humidity</b>	10 ~ 90% non-condensing
<b>Certification</b>	CE, FCC
<b>MTBF</b>	65,000 hrs

## Application



## Ordering Information

Model Name	Description
FRM220-2000MS	10/100/1000Base-T to 100/1000Base-X SFP web smart managed switch card. (Optional SFP)